



Equipment Specialist

REP-QUIP

1740 Hudson Bridge Road
Suite 1185
Stockbridge, Ga. 30281
Ph 770-320-7276
Fax 770-320-7277



Features RQ115HD

- Resurfaces Rotors, Drums and Flywheels
- Heavy iron casting provides a reliable base
- "One Cut" finish with variable feed speed
- Four arbor speeds
- Quick changeover from disc to drum
- Tapered roller bearings support drive shaft
- No bushings or sleeves to wear out
- High torque gear motors
- Automatic shutoff
- Adjustable work light

Technical Specifications

- Power required 115 volt—Drive motor 1HP 1725rpm
- Arbor speeds 85-110-140-185 rpm Carriage speed variable
- Drum diameter up to 30"- Drum travel to 9"
- Rotor/Flywheel diameter travel to 30" - facing travel up to 5"
- Rotor thickness up to 3"
- Arbor diameter standard 1" optional 1 7/8"
- Shipping weight 525 lbs

Features RQ215HD

- Resurfaces Rotors and Drums
- Quick changeover from drums to rotors
- 90 deg. Swivel head takes only a few seconds
- Single cut finish, speed preset at factory
- Heavy ductile iron construction
- Smooth running with efficient belt driven systems
- Comes with standard tooling

Technical Specifications

- Power required 115 volt—Drive motor 1HP 1725 rpm
- Arbor speed 190 rpm; Carriage speed .0025" per revolution
- Drum diameter up to 14"; Drum facing travel up to 4"
- Rotor diameter travel up to 18"; Rotor facing travel up to 4"
- Rotor thickness up to 3"
- Arbor diameter 1" , Optional arbor 1 7/8"

