Proudly Made
in the USA
Since 1917

Branick®

Spreaders

Large / Heavy Duty

Foot Operated Controls on all Large/HD Spreaders

The OTR, AG and Super Single Capable Model EF Spreader

Visit Our Website on your SmartPhone!

Features

- Tire Lift and Roll-On Spreaders for Faster, Easier Operation
- Spreaders for Everything From Passenger to OTR/AG
- Air Powered Spread Arms on All Large/HD Spreaders
- Quality All Steel Construction for Strength and Long Life
- Several Super Single Capable Models

TOUGH TIRES REQUIRE TOUGH EQUIPMENT!

Earl Branick designed the first Branick tire spreader with strength and long life in mind. Almost 80 years later we still make all our spreaders the same way, strong and durable. Our line of large and heavy duty spreaders all have air powered spread arms and all but the LR and S/FLL include a tire lift or adjustable height. The LR and LR/EF are the compact affordable option for commercial truck tires, while the 5500 provides a rock solid repair station and the AH/RI/R's power rotation makes it the best inspection spreader. The small but powerful S/FLL is the ideal service truck spreader and if you do a lot of work on big tough tires, the EF and EF/HD will do the job with ease. If you need a spreader, look no further than Branick. Manufactured at Branick's facility in Fargo, ND means you get American made quality and toughness.

www.branick.com 4245 Main Ave PO Box 1937 Fargo, ND 58107 Phone: 800.437.4394 Fax: 701.281.5900

© 2014 Branick Industries, Inc.

Branick®

Spreaders

Large / Heavy Duty

Specifications

	S/FLL	LR	LR/EF	AH/RI/R
Bead Diameter	OTR/AG	Up to 22.5”	Up to 22.5”	Up to 24.5”
Spread Arm Type	Air Powered	Air Powered	Air Powered	Air Powered
Spread Arm	Foot	Foot	Foot	Hand
Working Height	6”	27.75”	27.75”	Adj, 18” - 36”
Tire Lift / Roll On	Roll On	None	Lift	Roll On
Light	None	Included	Included	Included
Hook Adjustment	Lock Pin	Nylon Tip Set Screw	Nylon Tip Set Screw	Lock Pin
Shipping Wieght	177	210	280	570
Dimensions (inches)	35 W X 25 D X 16 L	41 W X 33 D X 45 L	41 W X 33 D X 45 L	47 W X 21 D X 44 L
Additional Information	Ideal for service truck Ground level spreader	LED light available	LED light available	Tire Inverter LED light available Reversible power tire rotation

Specifications (cont)

	5500	EF	EF/HD
Bead Diameter	Up to 24.5”	OTR/AG	OTR/AG
Spread Arm Type	Air Powered	Air Powered	Air Powered
Spread Arm Operation	Hand	Foot	Foot
Working Height	Adj. 14.25” - 36”	47.75”	47.75”
Tire Lift / Roll On	Roll On	Lift	Lift
Light	None	None	None
Hook Adjustment	Lock Pin	Semi-Automatic	Semi-Automatic
Shipping Wieght	460	480	795
Dimensions (inches)	29 W X 61 D X 45 L	60 W X 29 D X 78 L	63.5 W X 38 D X 79.5 L
Additional Information	Auto extend/retract ramp Tool tray with 4 air ports	Super single capable 360° tire rotation	Super single capable 360° tire rotation