



Proudly Made
in the USA
Since 1917



Branick® Spreaders Large / Heavy Duty

Foot Operated Controls
on all Large/HD Spreaders



The OTR, AG
and Super Single
Capable Model
EF Spreader

Visit Our Website!



Features

- Tire Lift and Roll-On Spreaders for Faster, Easier Operation
- Spreaders for Everything From Passenger to OTR/AG
- Air Powered Spread Arms on All Large/HD Spreaders
- Quality All Steel Construction for Strength and Long Life
- Several Super Single Capable Models

TOUGH TIRES REQUIRE TOUGH EQUIPMENT!

Earl Branick designed the first Branick tire spreader with strength and long life in mind. Almost 80 years later we still make all our spreaders the same way, strong and durable. Our line of large and heavy duty spreaders all have air powered spread arms and all but the LR and S/FLL include a tire lift or adjustable height. The LR and LR/EF are the compact affordable option for commercial truck tires, while the 5500 provides a rock solid repair station and the 5700's power rotation makes it the best inspection spreader. The small but powerful S/FLL is the ideal service truck spreader and if you do a lot of work on big tough tires, the EF and EF/HD will do the job with ease. If you need a spreader, look no further than Branick. Manufactured at Branick's facility in Fargo, ND means you get American made quality and toughness.

Branick®

Spreaders

Large / Heavy Duty



Specifications

	S/FLL	5300	5700E
Maximum Bead Diameter	OTR/AG	24.5"	24.5"
Maximum X-Section	16" / 406 mm	18" / 458 mm	18" / 458 mm
Spread Arm Type	Air Powered	Air Powered	Air Powered
Spread Arm Operation	Foot	Foot	Hand
Working Height	6"	31"	Adj, 15" - 32"
Tire Lift / Roll On	Roll On	Lift	Roll On Lifting Platform
Light	None	Included	Included
Hook Adjustment	Lock Pin	Detent Lock Pin	Lock Pin
Shipping Weight	190	350	660
Dimensions (inches)	35 W X 25 D X 16 L	34 W X 35 D X 38 L	47 W X 29 D X 65 L
Additional Information	Ideal for service truck Ground level spreader	Super single capable Locking Lift Tool Tray	Electric reversible rotation Tool tray with 4 air ports 2 electric outlets



Specifications (cont)

	5500	EF	EF/HD
Maximum Bead Diameter	24.5"	OTR/AG	OTR/AG
Maximum X-Section	18" / 458 mm	Up to and Including all 24.5	Up to and Including all 24.5
Spread Arm Type	Air Powered	Air Powered	Air Powered
Spread Arm Operation	Hand	Foot	Foot
Working Height	Adj. 14.25" - 36"	47.75"	47.75"
Tire Lift / Roll On	Roll On Lifting Platform	Lift	Lift
Light	None	None	None
Hook Adjustment	Lock Pin	Semi-Automatic	Semi-Automatic
Shipping Weight	441	500	800
Dimensions (inches)	29 W X 45 D X 61 L	60 W X 29 D X 78 L	64 W X 38 D X 80 L
Additional Information	Auto extend / retract ramp Tool tray with 4 air ports	Handles any road tire 360° tire rotation	Handles any road tire 360° tire rotation