



C-AIRE
COMPRESSORS

A050D120-3230

Electronic Control Panel
(2) 5 HP
2 STAGE

35.4 CFM @175psi

76" x 41" x 58"

970 RPM

1200 LBS.



- 3-5 Person Body Shop ■
- 4-7 Person Auto Repair Shop ■
- Truck Repair or Tire Shop ■
- Small Manufacturing Plant ■

Also Available:
**EXTENDED
WARRANTY KIT**

(Part# AX-V95)

*Two Warranty Kits required on duplex units



Commercial/Industrial Use

This duplex unit features an electronic control panel that uniquely balances run time equally between each pump, and ensures that neither pump is overworked from irregular air usage. It is perfect for applications where a 7.5HP simplex compressor is too small and has the added benefit of a built-in back up compressor for those who can't afford to be without air.

5 HP Three Phase 230v/460v Motor

- 12 Running amps (Requires 30 amp breaker)
- Pre-wired Magnetic Starter

Large Displacement 2 Cylinder Pumps

- Only 970 RPM
- 17.7 CFM @175 PSI each
- Solid Cast Iron Cylinders and Crankcase
- Rod inserts and Ball Bearing Mains

Electronic Control Panel

- Balances run time equally between pumps

120 Gallon Horizontal Tank

- ASME Certified
- Also available on 240 gallon horizontal tank

Fully Packaged, Fully Set!

Make sure your C-Aire compressor is set up correctly from the start! C-Aire's Fully Packaged Compressors include a factory installed Belt Guard Mounted Aftercooler and Moisture Minder Auto Tank Drain. This is the most affordable way to significantly reduce moisture and prolong the life and effectiveness of your pneumatic tools by removing approximately 60% of the moisture in your compressed air. Fully Packaged units also include an Installation Kit.



AFTERCOOLER

The Aftercooler is mounted directly to the unit's Belt Guard and utilizes the air drawn in by the flywheel for cooling before the air reaches the tank.



AUTOMATIC TANK DRAIN

The Automatic Tank Drain operates each time the compressor cycles, stores condensation without wasting air, prevents valves from fouling and reduces corrosion.



INSTALLATION KIT

4 Mounting Pads
4 Anchor Bolts
Steel Braided Flex Hose

NEXT SIZE **UP**



A075D120-3230

7.5 HP
2 STAGE
54.6 CFM
670 RPM
120 GALLON TANK
MAGNETIC STARTER

- 4-6 Person Body Shop
- 8-10 Person Auto Repair Shop
- Truck Repair or Tire Shop
- Small Manufacturing Plant

NEXT SIZE **DOWN**

A075V080-1230

7.5 HP
2 STAGE
27.3 CFM
670 RPM
80 GALLON TANK
MAGNETIC STARTER

- 2-3 Person Body Shop
- 3-5 Person Auto Repair Shop
- Small Manufacturing Plant
- Farm



Quality built... *because quality lasts.*