


ER71

MULTIFUNCTIONAL DIGITAL PANEL with Direct Weight Placement program and Behind Spoke (Split) mode

CEMB® PATENT

 VDD Virtual Direct Drive Quick measurement system



LASER and LED LIGHT for easy weight positioning inside the rim

 ELECTROMAGNETIC BRAKE holds the wheel in position


Made in ITALY



NEW AUTOMATIC ARM 2D to measure automatically diameters up to 30"

WIDTH SONAR 3D

for automatic measurement of wheel width (optional)



Power requirements

Balancing speed

Measuring cycle for 15 kg (33 lbs) wheel

Unbalance resolution

Rim width setting range

Rim diameter setting range

Max. tire diameter

Max. wheel weight

Shaft diameter

Machine weight

110 VAC, 50/60 Hz

100 rpm

4.7 s

< 0.01 oz (<1 g)

1.5" - 20" (40 - 510 mm)

10" - 30" (265 - 765 mm)

40" (1,016 mm)

165 lbs (75 Kg)

40 mm

354 lbs (160 Kg)

STANDARD ACCESSORIES

UC20/2 GLM40 41FF83150



MANUAL LOCKING















OPTIONAL ACCESSORIES

RL CUP - 41FF79255 SR-USA STUD ADAPT. - 41FF56189 SRU345 STUD ADAPT. - 41FFA6478 2-PIECE TRUCK CONE KIT - 41FF86174 UNIV. MOTORCYCLE ADAPT. - 41FF87401 WBL81 WHEEL LIFT - 46FL85170-KIT

CEMB® USA - BL Systems Inc.

2873 Ramsey Road, Gainesville GA 30501 - USA Phone +1 (678) 717-1050 - sales@cemb-usa.com www.cemb-usa.com

DISTRIBUTED BY