

CEMB[®] USA

SM628 BPS

Professional grade swing arm tire changers for OEM and oversized tires and custom wheel applications. Features an optional high-performance Bead Press System (BPS) which is highly recommended to easily aid in the servicing of low-profile, run flat, on/off road tires and commercial light trucks with stiff sidewalls and difficult rims with deep drop centers.

www.cemb-usa.com



PROUDLY DISTRIBUTED BY



SM628 BPS



Bead Press System

Provides simple servicing of stiff sidewall tires and deep drop center rims. Dual bead press aids save time and offers flexibility in multiple mounting method.



Table Top Clamping

Is self-centering with rim diameter index guides to aid in simple external rim clamping avoiding tire and rim scratches.

High Torque Motor

220v 2-speed motor and heavy-duty transmission handles the most difficult tires and deep drop center rims.

Polymer Mounting Head

Standard quick-change steel and polymer mounting head kit is supplied standard allows simple and fast change over from steel wheels to protection of alloy wheels.

Two Stage Inflation


Utilizes bead sealing jets optimized by placement at the clamping jaws.

Bead Breaker Shovel

Foot operated side mounted bead breaker shovel combines speed with power for everyday wheel applications to save time.



DIMENSIONS



Power Supply:	220V, 1ph, NEMA Plug L6-20P
Air Pressure:	145 psi (10 bar)
Rim Diameter (Ext.):	12" - 26" (6" ext.)
Tire Diameter:	44" (1117 mm)
Max. Wheel Width:	16" (406 mm)
Turn Table Speed:	8-15 rpm
Shipping Weight:	630 lbs (286 Kg)

CONTACT

CEMB[®] USA

CEMB USA - BL Systems Inc.
2873 Ramsey Road, Gainesville, GA 30501
(678) 717-1050 - sales@cemb-usa.com
www.cemb-usa.com