

N₂ >>> **FLOW 6000** **NTFS**



Full Service for up to six tires with the push of a button. Generates it's own N₂ using a unique PSA system (no need to rent tanks). Just connect to shop air, select the desired tire pressure and Start Service.

Automatically deflate and fill tires with N₂ using (2) purge cycles. Once done, a buzzer will indicate the service is complete. Then, the onboard display shows the percentage of N₂ in the tires.

Smaller, Lighter, Faster and Cost Effective

- **Power supply 120 VAC to 12 volt system**
- **Optional portability**
Rechargeable 12 volt battery
- **Completely Automatic**
Press a button and walk way. A buzzer indicates completion of service
- **Service Time**
Less than 10 mintues for most vehicles
- **No Need for additional N₂ Purity Tester**
Percentage of N₂ in tires displayed at the end of each service on panel.
- **Manual fill feature**
Allows for top off or quick manual N₂ inflation
- **Low Maintenance**
Pre Filters protect sieve towers, indicator signals when to change filters



Easy 8-Step Operation

- 1** - Connect shop air supply to Nitrogen Generator (minimum 120 PSI) and plug into 120 VAC outlet
- 2** - Turn ON Power (button located at the top center of Face Panel) this will start a 15 second CALIBRATION cycle, you will then see -2500 Calibration is Complete
- 3** - Push the START N_2 CHARGE button the Generator will immediately start producing N_2 and storing 98.0 to 99.8% N_2 in 20 gallon storage tank.
- 4** - Connect 4 to 6 hoses to vehicle's tire valve stems
- 5** - Select tire Pressure by pressing the arrows UP or DOWN
- 6** - Press START SERVICE button
- 7** - In Just a few short minutes, a buzzer will sound, the SERVICE IS COMPLETE light will illuminate. Press the PAUSE button to stop the buzzer sound. The percentage of N_2 in the tires will display in the left window
- 8** - Disconnect all hoses. Service is now Complete



System Specifications

N_2 Purity	98.00 - 99.8% (94% minimum in tires)
N_2 Output	10 CFM
Power Source	120 VAC
Temperature Range	-15° F to 160° F
Internal N_2 Storage Tank	20 Gallons
Tires Inflated	1 - 6 (4 hoses included)
Weight	181 lbs w 4 hoses
Dimensions	23.5" W x 48" H x 29" D