

SUPPORT STANDS



Built to meet or exceed ASME PASE 2014 standards. The positive pinning stands are durable, long-lasting and reliable.

Models in this section:

- CSS-7 Support Stands
- CSS-10 Support Stands
- CSS-12 Support Stands
- CSS-25 Support Stands
- CSS-35 Support Stands
- CVS-7H Support Stands – High Rise
- CVS-9H Support Stands – High Rise
- CVS-10H Support Stands – High Rise
- CTR-20 Truck Ramps – Non-Skid



- 485 80004 00 CSS-7 7.5 Ton Support Stand**
- 485 80005 00 CSS-7T 7.5 Ton Support Stand – Tall**
- 485 80006 00 CSS-10 10 Ton Support Stand**
- 485 80007 00 CSS-10T 10 Ton Support Stand – Tall**
- 485 80008 00 CSS-12 12 Ton Support Stand**
- 485 80009 00 CSS-12T 12 Ton Support Stand – Tall**
- 485 80010 00 CSS-25 25 Ton Support Stand**
- 485 80011 00 CSS-25T 25 Ton Support Stand – Tall**
- 485 80012 00 CSS-35 35 Ton Support Stand**
- 485 80014 00 CSS-35P 35 Ton Support Stand w/ Plate**
- 485 80013 00 CSS-35T 35 Ton Support Stand – Tall**
- 485 80015 00 CSS-35A 35 Ton Support Stand w/ Air Assist**
- 485 80016 00 CSS-35AT 35 Ton Support Stand w/ Air Assist – Tall**

Model	Capacity	Minimum Start Height	Maximum Lift Height	Adjustment Increments	Shipping Wt. Per Pair
CSS-7	15,435 lb (7,001 kg)	9.5 in (25 cm)	16 in (41 cm)	1 in (3 cm)	32 lb (15 kg)
CSS-7T	15,435 lb (7,001 kg)	12 in (30 cm)	20 in (51 cm)	1.5 in (4 cm)	38 lb (17 kg)
CSS-10	20,000 lb (9,072 kg)	20 in (51 cm)	32 in (81 cm)	1 in (3 cm)	70 lb (32 kg)
CSS-10T	20,000 lb (9,072 kg)	30 in (76.2 cm)	52 in (132 cm)	1 in (3 cm)	158 lb (72 kg)
CSS-12					
CSS-12T					
CSS-25	50,000 lb (22,680 kg)	12 in (30 cm)	20 in (51 cm)	1.5 in (4 cm)	62 lb (28 kg)
CSS-25T	50,000 lb (22,680 kg)	20 in (51 cm)	32 in (81 cm)	1.5 in (4 cm)	112 lb (51 kg)
CSS-35	70,000 lb (31,751 kg)	13.5 in (34 cm)	21 in (53 cm)	1.5 in (4 cm)	84 lb (38 kg)
CSS-35P	70,000 lb (31,751 kg)				
CSS-35T	70,000 lb (31,751 kg)	21 in (53 cm)	33.3 in (85 cm)	1.5 in (4 cm)	129 lb (59 kg)
CSS-35A	70,000 lb (31,751 kg)	20.3 in (51.4 cm)	34.8 in (88.2 cm)	1 in (2.5 cm)	136 lb (61.7 kg)
CSS-35AT	70,000 lb (31,751 kg)	31.6 in (80.2 cm)	55.4 in (140.7 cm)	1 in (2.5 cm)	194 lb (87 kg)