

HSP Series

Hot Water – Gasoline – Direct Drive

Pump:

Preset stainless-steel and brass unloader valve |
Forged brass manifold | Thermal relief valve |
Low pressure detergent injector (Available as an
option on HSP-2503-0MMH)

Frame:

Reinforced powder coated steel tube frame with center
balanced lift | Convenient gun/wand holder and hose
wrap | 13-inch flat-free tires

Components:

Top-fired powder coated heat exchanger | No. 1 or
No. 2 diesel or kerosene fired burner (Not approved
for bio-fuel)

Miscellaneous:

Temperature rise 150°F/66°C above ambient, maximum
outlet temperature is 200°F

Unit Includes:

Quick connect nozzles - 0°, 15°, 25° and 40° |
50-foot x 3/8-inch steel wire-braided high pressure hose
with quick connects | Professional-grade insulated
trigger gun with safety lock-off | Adjustable pressure
insulated dual lance

Limited Warranties:

3 year coil | 3 year Honda and Kohler engines |
7 year AR and Mi-T-M pumps

Certification:

CSA Certified - US and Canada



HSP-3504-3MGH



The Electro Magnetic Firing (EMF) system of the HSP Series, along with its unique burner design, makes this popular hot water pressure washer one of the most "in-demand" in the industry. It's a great solution for removing heavy mud from construction and ag equipment.

| MODEL NUMBER | PSI | GPM | DISPLACEMENT/ENGINE | PUMP | Mi-T-M NO. | FUEL TANK CAPACITY | BURNER FUEL TANK CAP. | BURNER FUEL CONS. | BTU PER HOUR | DIMENSIONS (LxWxH) | SHIP WT. | NET WT. |
|---------------|------|-----|------------------------|---------------------|------------|--------------------|-----------------------|-------------------|--------------|--------------------|----------|---------|
| HSP-2503-0MMH | 2500 | 2.6 | 196cc Honda GX200 OHV | Mi-T-M | 3-0417 | 0.95 gallon | 4.0 gallons | 1.53 gph | 210,000 | 43x29.5x36.5in. | 411 lb. | 295 lb. |
| HSP-3003-3MGH | 3000 | 2.9 | 270cc Honda GX270 OHV | AR, external bypass | 3-0241 | 1.59 gallons | 5.5 gallons | 1.84 gph | 253,000 | 43x30x41in. | 530 lb. | 407 lb. |
| HSP-3504-3MGH | 3500 | 3.3 | 389cc Honda GX390 OHV | AR, external bypass | 3-0194 | 1.70 gallons | 5.5 gallons | 2.14 gph | 294,000 | 43x30x41in. | 551 lb. | 428 lb. |
| HSP-3504-3MGK | 3500 | 3.3 | 429cc Kohler CH440 OHV | AR, external bypass | 3-0194 | 1.70 gallons | 5.5 gallons | 2.14 gph | 294,000 | 43x30x41in. | 551 lb. | 428 lb. |

Accessories & Options:

| PART NUMBER | DESCRIPTION | FITS MODELS | PART NUMBER | DESCRIPTION | FITS MODELS |
|-------------|-------------------------------------|-------------------------|-------------|------------------------------------|-------------------------|
| 20-0464A52 | Rain cap | 3000 to 3500-PSI models | HX-0234 | Low pressure detergent injector | HSP-2503-0MMH |
| 50-0161 | High pressure detergent injector | All models | HX-0236 | Hour meter | HSP-2503-0MMH |
| 850-0433 | 50-ft. x 3/8-in. high pressure hose | 3500-PSI models | HX-0274 | Rain cap | 3000 to 3500-PSI models |
| 851-0262 | 50-ft. x 3/8-in. high pressure hose | 2500 to 3000-PSI models | HX-0279 | Hour meter | 3000 to 3500-PSI models |
| HX-0098 | Electric start - battery included | HSP-3504-3MGH | HX-0280 | Adjustable thermostat | 3000 to 3500-PSI models |
| HX-0233 | Adjustable thermostat | HSP-2503-0MMH | HX-0281 | Hour meter / adjustable thermostat | 3000 to 3500-PSI models |

PRESSURE WASHERS

