BRAD Breathing Air Systems

The Best Dry You Can Buy! ™



A-63

Our products are

Made in the USA.

BRAD-01B

Complete System Package
Prefilter Combo, CO Monitor, Belt Regulator, Full Face Mask,
35' Hose Assembly, ½ "Regulator w/Gauge

FEATURES

- Produces Grade "D" Breathable Air
- Ultra Lightweight Design
- 35 Feet of Low Odor Non "Gassing" Breathing Assembly Air Hose
- Belt Mounted Full Diaphragm Regulator
- Safest AFF-50 Rated Mask Ensures Safety of the User
- BRAD-M1 Full Face NIOSH Approved Breathing Mask (TC#19C-353)
- Double the Assigned Protection Factor (APF) of Competitor Supplied Air Hoods
- Over-the-Shoulder Design Air Breathing Tube
- High Flow Push-to-Make Connectors
- Convenient flip up BRAD-M2 Mask available
- Self Calibrating Monitor w/Audible Alarm; Displays
 Actual CO Levels & Alarms at 10ppm of CO
- Monitor comes with 12 Volt Battery Back-up
- Less Air Needed (3-4 scfm) to Feed BRAD-M1 Mask

Operating kit provides the safest NIOSH approved mask design with 35' air supply hose. Unit is light weight and mask provided has a wide field of vision. It's the safest supplied air respirator offered. Meets OSHA standards [29CFR 1910.134(d)(1)]. CO Meter, Explosion Proof Rating of Class 1, Div 1, Groups A, B, C, D.



Prefilter Combo & CO Monitor



For BRAD-01B Package with BRAD-M2 Flip-up Mask, add a "1" to end of part number (BRAD-01B1)

2 Man System Packages

The Best Dry You Can Buy! ™

BRAD-PC2B

Prefilter Combo & CO Monitor for 2 Man System



BRAD-02B

Prefilter Combo & CO Monitor for 2 Man System with (2) BRAD-OK operator kits



BRAD-02B1

Prefilter Combo & CO Monitor for 2 Man System with (2) BRAD-FM7 operators kits



I Year Supply of Replacement Elements: **BRAD-02-MK**

Desiccant Breathing Air Systems

The Best Dry You Can Buy! ™

BRAD-PC3B

Prefilter Combo, CO Monitor & Desiccant Dryer



BRAD-4000B

Complete System Package with Desiccant Dryer Includes: Prefilter combo, desiccant tower, CO Monitor, BRAD-OK operators kit



BRAD-4000B1

Complete System Package with Desiccant Dryer Includes: Prefilter combo, desiccant tower, CO Monitor, BRAD-FM7 operators kit



I Year Supply of Replacement Elements: BRAD-4000-MK

BRAD Masks & Operator Kits

The Best Dry You Can Buy! ™



BRAD-M1Full face Mask



BRAD-M2Convenient flip- up mask

BRAD-OK

Operators Kit Includes Full face mask, 35' hose assembly, and belt regulator



BRAD-FM7

Operators Kit Includes Full face mask, 50' hose assembly, and flow control valve



BRAD Accessories

The Best Dry You Can Buy! ™

BRAD-CM2

CO monitor in BRAD-01B systems



BRAD-01B-MK

l Year Replacement Element Kit



MR-1

Mini paint gun regulator with gauge



BRAD-02B-MK

l Year Replacement Element Kit



BRAD-M1-LC

Full face mask peel off replacement lens covers



BRAD-4000B-MK

l Year Replacement Element Kit



BRAD-M2-LC

Flip-up mask peel off replacement lens covers



BRAD-FCV

Flow Control Valve



BRAD-060-M04

Prefilter for BRAD-01B systems



BRAD-H35

35' Breathing Air Hose



BRAD-150-M04

Prefilter for BRAD-02B Systems



HVHA-B35

35' Operator Hose 3/8" w/ Quick Disconnects



BRAD-PERF 25B/50B

The Best Dry You Can Buy! ™

CLEAN, DRY SPRAY & BREATHING AIR SUPPLY

FEATURES & BENEFITS:

- Consistent -40°F Dew Point Air(or better) to the Gun Preferred by Paint MFR's
- Delivers Perfectly Clean, Dry Air for "Flawless Finishes Every Time"
- Has the Most Activated Carbon of Any Competitive Breathing/Paint Air System on the Market
- Engineered for Use with All Paint Spray Guns (not included) Especially HVLP Guns
- Supplies Grade D Breathing Air
- PERF-BRAD-25B Model for Single Gun Spraying; BRAD-PERF-50B for Two Gun Spraying Booths
- Regenerative Desiccant Beds Require Little Maintenance
- Monitor Design is Directly Inline with the Air Flow Ensuring Consistant, Safe Monitoring.
- Self Calibrating Monitor w/Audible Alarm
- Monitor Displays Actual CO Levels & Alarms at 10ppm of CO

BRAD-PERF-25B



- BRAD-PERF-25B, 150 scfm pre-filter system, with auto drain 1st stage, $\frac{1}{2}$ "NPT Inlet, $\frac{3}{8}$ " FPT outlet to gun. 25 scfm Regenerative Dryer
- BRAD-PERF-50B, 150 scfm pre-filter system, with auto drain 1st stage, $\frac{1}{2}$ " NPT Inlet, $\frac{1}{2}$ " FPT outlet to guns. 50 scfm Regenerative Dryer

See operator kits sheet on previous pages for more options & information. Repair & maintenance sheet also available for review



BRAD-PERF 25B/50B

The Best Dry You Can Buy! ™

BRAD-PERF-25B

BRAD-PERF-50B



RTi Patented 2-Stage PreFilter w/CO Monitor

- PN: BRAD-PC2B
- 150 SCFM @ 100 PSI
- ½" Ball Valve Inlet
- Auto Drain 1st Stage
- Power Pack w/Battery Back-up Supplied w/Monitor
- The MOST Activated Carbon in any Competitor's System on the Market
- Replacement Elements:

1st Stage: PN: DE362C 2nd Stage: PN: 3C-151

Both 25 & 50 Models Utilize the BRAD-PC2B

Desiccant Dryer



- PN: ARAD-25
- Regenerative Desiccant Dryer Uses Dry Air Purge to recondition desiccant bed, No need to change your desiccant!
- Up to 25 SCFM @ 100 PSI
- -40°F Dew Point
- 3/8" Inlet/Outlet
- Inlet Flow: 29 SCFM Max
- Moisture Indicator @ Outlet
- Uses < 0.1 Amps
- Fused Overload Protection
- 110 VAC w/ 5' Power Cord
- NEMA 4 Enclosure
- Easy Wall Mount Design
- Quiet Operation
- Aluminum Towers No Rust



- PN: ARAD-50
- Regenerative Desiccant Dryer Uses Dry Air Purge to recondition desiccant bed, No need to change your desiccant!
- Up to 50 SCFM @ 100 PSI
- -40°F Dew Point
- 3/8" Inlet/Outlet
- Inlet Flow: 54 SCFM Max
- Moisture Indicator @ Outlet
- Uses < 0.1 Amps
- Fused Overload Protection
- 110 VAC w/ 5' Power Cord
- NEMA 4 Enclosure
- Easy Wall Mount Design
- Quiet Operation
- Aluminum Towers No Rust

After Filter & Accessories



- PN: PERF-25-AF
- 60 SCFM @ 100 PSI
- 3/8" Inlet/Outlet
- Capacity .01 micron@ 99.9998% efficiency
- Eliminates Desiccant Dust Contamination of Paint
- Manual Petcock Drain
- ¾" High Flow Regulator with Gauge

Additional Accessories (not shown):

- HVHA-35 Hose Assembly
- MR-1 Mini Regulators



- PN: PERF-50-AF
- 60 SCFM @ 100 PSI
- 1/2" Inlet/Outlet
- Capacity .01 micron
 @ 99.9998% efficiency
- Eliminates Desiccant Dust Contamination of Paint
- Manual Petcock Drain
- 1/2" High Flow Regulator with Gauge
- •2 Port Manifold with 3/8" Outlet Ball Valves

Additional Accessories (not shown):

- (2) HVHA-35 Hose Assembly
- (2) MR-1 Mini Regulators